

Air Top 2000 ST

Universal air heater for drivers' cabs and small cargo holds



The multi-purpose, affordable, and powerful heating solution.

Users can switch between air circulation and fresh air as desired – the air is warmed quickly and quietly to the desired temperature in either operating mode.

- 2 kW of power for quick and even heat distribution in drivers' cabs and small cargo holds
- Low price and low operating costs
- Quick and easy installation due to universal delivery of all accessories
- Also suitable for ADR transport vehicles (dangerous/toxic substances)



Truck



Light-duty Vehicles



Bus



Rail



Off-Highway



Defense



Special Vehicles

Technical specifications for heaters

		Air Top 2000 ST	
		Diesel	Petrol
ECE approval number	ECE R122 (heater)	E1 00 0216	
	ECE R10 (EMC)	E1 03 6196	
EG type approval number	(heater)	e1*2001/56*2006/119*0022*06	
	(EMC)	e1*72/245*2009/19*1085*__	
Heating performance (kW)	Control range	0.9 - 2.0	
Fuel consumption (kg/h)	Control range	0.12 - 0.24	0.14 - 0.27
Nominal voltage (V)		12/24	12
Nominal power consumption (W)	Control range	14 - 29	
Heater through flow volume (m³/h)	Approx. 0.5 mbar	93	
Fuels		Diesel EN 590 PME DIN EN 14214 Heating oil EL	Petrol EN 228
Operation temperature range (°C)		-40 to +40	
Measurements L x W x H (mm)		311 x 120 x 121	
Weight (kg)		2.6	

Heater controls:

- Switch with function display

Simple on/off switch for the additional (parking) heater



- Digital timer 1531, standard timer

Temperature selection, programming of up to three separate start times; alarm options available

