

SG-5000 SERIES

 high performance generator set range for marine containers —

214

No. solar

THE

Protecting cold chain integrity



SG-5000 YOUR INDEPENDENT POWER SOURCE

Temperature sensitive cargoes require independently powered units that keep running whatever conditions, temperatures or delays they have to contend with. Units that support a sustainable operation, and offer the precise temperature controls needed to avoid spoilage or thermal damage – while also safeguarding product quality.

Manufactured in the USA, the Thermo King SG-5000 is a powerful generator set for **marine reefers** that offers a rich mix of performance, low running costs, and no-compromise load protection.

Benefiting from a highly reliable and efficient power source, this premium genset is also **long-term CARB compliant**. Available in both clip-on and undermount formats, the SG-5000 is designed to power all ISO reefers on the market.

TRUE RELIABILITY

Delivered via a proven, high performance engine and a generator built for stability.

LONG-TERM COMPLIANCE Fully CARB and EPA compliant to help simplify fleet management.

TOTAL COST OF OWNERSHIP The modular design maximizes operational efficiency while helping lower maintenance costs.

INTELLIGENT OPERATION

With an advanced controller that combines simple, easy to use navigation with advanced diagnostics.


CONFIGURATIONS & SPECIFICATIONS

Including both clip-on and undermount options, the SG-5000 offers solutions for a variety of different applications.

P. 4 P. 6 P. 8

P. 9

P. 10



New capabilities, improved reliability

Featuring a proven ultra-powerful engine and high specification generator, the SG-5000 can be uniquely trusted to deliver certainty of operation. In fact, this complete genset incorporates a wide variety of innovations and upgraded components to ensure its position as the most dependable refrigerated power supply available for reefer units.

A GENERATOR DESIGNED FOR EFFICIENCY

The SG-5000 incorporates a large diameter alternator with reinforced bearings and high specification rotating diodes. Plus there's an engine-driven coolant fan and premium corrosion protection to ensure fail-safe operations 24/7.

- Ultra tough 190mm synchronous 4-poles alternator with brushless exciter
- Lower duty cycles (compared to 120mm/145mm models) increase durability and longevity
- Stable voltage control, through an intelligent digital regulator

ENGINE TYPE	High Pressure Common Rail (cast iron)
POWER with additional p	22kw – delivering 15kw as per ISO standards, ower for use in extreme conditions to provide extra load protection
POWER ADVANTAGE OVER CO	MPETITION 16%
OPERATIONAL DURATION	25,000 hours (with normal maintenance)
TESTED TO WORK	-40°C and 50°C, and up to 3,000 meters altitude
AUTO RESTART	to provide maximum load protection
HIGH TORQUE ADVANTAGE	ensures energy is consistently available under any load conditions
SIMPLIFIED MAINTENANCE	no turbocharger or related components
WATER SEPARATION SYSTEM	reduces the risk of water returning to the fuel tanks
IMPROVED FUEL FILTRATION	delivers a 10x improvement in fuel quality to injectors







Getting and staying compliance ready

Reducing emissions throughout the cold chain is obviously an important and worthwhile objective. The challenge comes from ensuring all units meet local and regional standards. Get this right and you can align the right assets to the right journey, maximize fleet utilization, and avoid the cost of expensive retrofits.

MAINTAIN FULL **EPA TIER 4 COMPLIANCE**

Tier 4 compliance standards for offhighway diesel engines are the strictest emissions requirement currently listed by the Environmental Protection Agency (EPA). The regulation is particularly focused on particulate matter and nitrogen oxide emissions, and was fully implemented in 2015. As with the CARB regulations, Thermo King's SG-5000 enables compliance with EPA Tier 4.




Transforming your total cost of ownership

Talking TCO with the SG-5000 starts with the value of long-term compliance, which removes the need to relocate older units outside of California to avoid the potential for non-compliance.

CLIP-ON

The self-contained unit clips on to the corner castings with quick- disconnect fasteners or an optional header pin mounting.



UNDERMOUNT

The undermount SG can be fitted in two ways, to suit the specific needs of the operator.

A HOST OF PRACTICAL BENEFITS

With clip-on and undermount options the SG-5000 can connect to any reefer your fleet possesses and offers maximum operational flexibility:

- Clip on corner castings enhances operational efficiency and ease of use
- Common components drive down costs and improve ease of service
- Accessible undermount unit lowers service and maintenance costs



SUPPORT WHEN YOU NEED IT MOST

Supporting your TCO calculation is the world-class service and parts support available from Thermo King's international dealer network.

Dealers that are:

- Extensively trained
- Highly experienced
- Certified to exacting Thermo King standards

THE SG-5000 UP AND DOWN REPORT

HIGHER EFFICIENCY

- More fuel efficient engine with faster throttle response
- Eco power as standard with integrated 2-speed fuel saving technology
- Extended service intervals stretching to 3,000 hours for scheduled maintenance

LOWER WEIGHT

- Clip-on configuration
 828kg
- Undermount configuration
 686 kg



Monitor and respond to conditions with confidence

With an advanced controller, the SG-5000 offers the **intelligence and control** to safeguard loads across any journey and ambient conditions. From accessing alarms to monitoring temperatures, the genset offers **easy-to-use interfaces** and intuitive management capabilities.

USER-FRIENDLY DISPLAY

- Backlit LCD digital display screen
- Simple, sturdy navigation keypad
- Multi-language capabilities,
- with English and Spanish languages as standard

SMART DIAGNOSTICS

- Automated pre-trip testing
- Advanced self-check features, including alarms
- Data logging of events, alarms, and messages
- Hardware enabled to support 3rd party telematics

SIMPLE DESIGN

- Manual test functionality
- Built-in battery charger
- HMI separate from control box

TELEMATICS

- Real-time monitoring and management on rail, by road or at terminal
- Optional fuel sensor works even if the Genset is off
- Factory mounted installation (can retrofit Gensets already in the field)
- Easy and seamless interface with 3rd party systems



Configurations & specifications

CONFIGURATIONS



CLIP-ON

The self-contained unit clips on to the corner castings with quick- disconnect fasteners or an optional header pin mounting.

SPECIFICATIONS


ENGINE	TK diesel engine co
FUEL TYPE	No. 2 diesel (under nor
ROTATIONAL SPEED	
GENERATOR	
OUTPUT POWER	
APPARENT POWER	
ROTATIONAL SPEED	
ELECTRICAL SYSTEM	
BATTERY	
FUEL TANK	
SGCO	
SGCM	
SGSM	
WEIGHT - LESS FUEL	
SGCO	
SGCM	

UNDERMOUNT

The undermount SG can be fitted in two ways, to suit the specific needs of the operator.



DIMENSIONS



Dimensions in millimeters

compliant with EPA Tier 4 and CARB regulations

ormal conditions)No. 1 diesel (cold weather fuel)

500 ±25rpm1800 ±25rpm

460/230Vac, 3Phase, 60Hz

15kW

18.75 kVA

1800rpm

SG+ microprocessor controller

12V, 925CCA

Included in all models

473l (125gal) 302l or 198l (80gal or 50gal) 302l or 198l (80gal or 50gal)

871kg(1920lbs) 653kg(1440lbs) 50gal tank 680kg(1500lbs) 80gal tank







Thermo King – by Trane Technologies (NYSE: TT), a global climate innovator – is a worldwide leader in sustainable transport temperature control solutions. Thermo King has been providing transport temperature control solutions for a variety of applications, including trailers, truck bodies, buses, air, shipboard containers and railway cars since 1938.

For further information, please visit: thermoking.com

Find your nearest dealer on dealers.thermoking.com

Tare - the second second

Thermo King – Lenneke Marelaan 6, B-1932 Sint-Stevens-Woluwe, Belgium © 2024 Thermo King TK 80051 (05-2024)-EN3