

COLDCUBE™ CONNECT TECHNISCHE DATEN

TK-NR.	6100235	6100236	6100237	6100238	6100239	6100240	6100241	6100242	6100243	6100244	6100245	6100246	6100247	6100248	6100249	6100250	
Bruttovolumen (Liter)	32	32	82	82	140	140	140	140	330	330	330	330	720	720	720	720	
Temperaturbereich (°C)	> -24 °C	+40°C bis -24°C	> -24 °C	+40°C bis -24°C	> -10 °C	+30°C bis -10°C	> -21 °C	+30 °C bis -21 °C	> +0 °C	+30 °C bis +0 °C	> -21 °C	+30 °C bis -21 °C	> +0 °C	+30 °C bis +0 °C	> -24 °C	+30 °C bis -24 °C	
Automatischer Kühl-/Heizbetrieb	Nein	Ja	Nein	Ja	Nein	Ja	Nein	Ja	Nein	Ja	Nein	Ja	Nein	Ja	Nein	Ja	
Spannung	12–24 VDC	12–24 VDC	12–24 VDC	12–24 VDC	12–24 VDC	12–24 VDC	12–24 VDC	12–24 VDC	12–24 VDC	12–24 VDC	12–24 VDC	12–24 VDC	12–24 VDC	12–24 VDC	12 VDC	12 VDC	
Spitzenstrom (bei 12 VDC)	9	9	9	9	10	10	18	18	10	10	18	18	20 A	20 A	32 A	32 A	
Sicherung an DC-Kabel	16 A	16 A	25 A	25 A	30 A	30 A	50 A	50 A	30 A	30 A	30 A	30 A	50 A	50 A	50 A	50 A	
Abmessungen außen (mm)	670 × 390 × 480		940 × 560 × 551		1000 × 620 × 710				1020 × 1000 × 1000				1400 × 1100 × 1100				
Gewicht (kg)	22,5	22,5	35	35	52	54	55	57	80	83	83	86	144	147	150	153	
PU-Isolierung (mm)	65-70		80		80-100				100								
Isolierungsfaktor „K“	n/v		0,32 W/m²K		0,35 W/m²K				0,27 W/m²K				0,28 W/m²K				
Kompressor (Modell)	BD50F	BD50F	BD50F	BD50F	BD50F	BD50F	BD80F	BD80F	BD50F	BD50F	BD80F	BD80F	BD80F	BD80F	BD80F	BD220CL	BD220CL
Kältemittelgas (Typ)	R134a	R134a	R134a	R134a	R134a	R134a	R134a	R134a	R134a	R134a	R134a	R134a	R134a	R134a	R134a	R-404A	R-404A
Kältemittelgas (Gramm)	60	60	65	65	65	65	120	120	96	96	130	130	133	133	305	305	
Batterieaus-/einschaltung (VDC)	9,6–10,9	9,6–10,9	9,6–10,9	9,6–10,9	9,6–10,9	9,6–10,9	9,6–10,9	9,6–10,9	9,6–10,9	9,6–10,9	9,6–10,9	9,6–10,9	9,6–10,9	9,6–10,9	9,6–10,9	11,0–12,3	11,0–12,3

