





Proven reliability across the seas

Thermo King creates innovative temperature control solutions that help your fleet perform more efficiently. CFF is the culmination of our deep container refrigeration knowledge acquired from the intermodal use of reefer units on rough roads and even rougher seas.

Our new CFF unit features improved temperature and humidity control, lower total cost of ownership and the implementation of a low pressure, lower GWP refrigerant. The results speak for themselves. The worldwide reference for marine reefer refrigeration.





-30°C to +30°C

CHOOSE YOUR OPTIMAL SET-POINT

CFF can reach and maintain box temperature in the toughest conditions between -30°C and +30°C to safeguard product quality.

+25 years

DESIGNED TO LAST LONGER

CFF makes use of proven technology – the characteristic V-shape picture frame has been a frontrunner in the market for 25+ years. Its unique design allows for optimal heat exchange, system efficiency and easy service access.

24/7 support

SERVICE AROUND THE WORLD

From planned maintenance to unscheduled repairs – Thermo King's extensive service network provides superior parts availability and **around the clock support**.

Raising reefer performance since the 1950s

At Thermo King, we take pride in CFF and what it offers to our customers. Here are the 5 main reasons to choose our industry-leading solution:

- 1 PRECISE TEMPERATURE CONTROL The unique CFF advanced temperature management control system delivers extremely precise temperature control +/- 0.25°C in chilled mode and +/- 1°C in frozen mode.
- (2) FAST PULL-DOWN Thanks to its superior cooling capacity, CFF can reach specific set-points faster and increase the storage life of your shipments.
- LESS ENERGY CONSUMPTION CFF comes with the industry-standard R-134A and is 100% ready for R-513A as a drop-in. Both are lower Global Warming Potential refrigerants that enable an optimal Coefficient of Performance and drastically reduce your energy cost.

(3) LOWER GWP REFRIGERANTS FOR

- (4) THERMO KING PARTS LAST LONGER Every component is crucial to the overall performance of your unit. Genuine Thermo King consumables and replacement parts are created with high-quality materials and rigorously
- (5) SMART ENERGY MANAGEMENT CFF offers remarkable energy efficiency through intelligent controls and component design - without compromising on load protection.



environmental impact.

– 5

SMART CONTAINERS. SMARTER CHOICES.

Unique and customizable cold-chain technology



SEAMLESS CONNECTIVITY

CFF's MP-4000 controller is compatible with a wide range of telematics solutions for both one-way and two-way communication. It features a built-in Remote Monitoring Module that can interface with the advanced wireless remote monitoring system of your choice.



SMART PTI: AUTOMATED PERFORMANCE AUDITS

Smart PreTrip Inspection can be enabled to save you time and money. The intelligent MP-4000 controller will perform full inspections during reefer operation – anytime or anywhere, empty or loaded.



ADVANCED FRESH AIR MANAGEMENT

TK FRESH+ protects fresh produce from detrimental atmospheric conditions.

Just indicate your desired fresh air rate on the MP-4000 controller and TK FRESH+ will ensure the specified fresh air rates are maintained. Air vent logging (AVL) will also document the actual air exchange process.





SYNCHRONIZED DEFROST

Simultaneous defrost cycles for adjoining reefers are critical for optimum cooling performance and energy efficiency.



COMPATIBLE WATER-COOLED CONDENSERS (OPTION)

When air cooling capacity is insufficient – e.g. below-deck – water-cooled condensers offer a reliable and compatible alternative while reducing power consumption.



REAL DATA FOR REAL DECISIONS

Energy data logging keeps you informed about real-life power consumption, so you can make better decisions about power usage than ever before.



SHOW OFF YOUR STYLE

Proudly display your brand around the world by customizing the visual aspects of your CFF units with your logo, decals, and colors.

MP-4000 controller: helping you run a tighter ship

Every CFF unit comes equipped with an MP-4000 controller – boasting advanced control algorithms, a faster processor and the implementation of ultraprecise PT1000 control sensors. The uniquely intelligent MP-4000 controller is one of the main driving forces behind the CFF's ability to deliver best-in-class temperature control with an accuracy of up to +/-0.25°C.



ECO-MODE EFFICIENCY

Engage the optimized power consumption mode to consume less energy and activate a wider temperature spread without compromising your cargo. Depending on your chosen set-point and the ambient temperature, the CFF sets new standards in operating efficiency and gives you the potential for significant cost and fuel savings.



RENOWNED USABILITY

The MP-4000 has been used on the MAGNUM PLUS® for 10+ years and has been widely praised among its users for its usability – which is why the CFF will feature the same:

- alarm and warning codes
- PreTrip Inspections
- · option set
- · text rich definitions
- screen flow
- · software customization capability



CERTIFIED 2-WAY CONNECTIVITY

The MP-4000 features a built-in **Remote Monitoring Module** that you can enable through software. As a result, the controller can interface with the advanced wireless remote monitoring system of your choice. The MP-4000 controller also features a **data logger** to record temperatures, humidity, air-exchange, CO₂/O₂, pressures, events, PTI results, and power consumption for each trip.



SYSTEM NET COOLING CAPACITY FULL COOL CFF MODEL - AIR COOLED CONDENSING

SETPOINT	460V, 3 Phase, 60 Hz Power			
	NET COOLING CAPACITY		POWER CONSUMPTION	
	Capacity BTU/hr	Capacity kW	Power kW	
21.1°C (70°F)	53,618	15,700	10,650	
1.7°C (35°F)	38,847	11,375	8,800	
-17.8°C (0°F)	21,601	6,325	5,690	
-28.9°C (-20°F)	13,780	4,035	4,570	

System net cooling capacity with a $\,37.8^{\circ}\text{C}\,(100^{\circ}\text{F})$ ambient air temperature.

EVAPORATOR AIRFLOW SPECIFICATIONS SYSTEM NET HEATING CAPACITY

CFF	460V, 3 Phase, 60 Hz Power		380V, 3 Phase, 50 Hz Power		
	HEATING CAPACITY				
	Watts	BTU/hr	Watts	BTU/hr	
	5,250	17,914	3,900	13,300	

System net heating capacity includes fan heat.

DOWNLOAD THE COMPLETE CFF MANUAL ONLINE

Stay supported by your Thermo King dealer

The Thermo King dealer network boasts over 460 authorized service points throughout the world – all are open and available 24/7.